ViewSonic®

VE170 LCD Display

ViewPanel® Series

- **Full 17" viewable screen**
- **1,280 x 1,024 true resolution**
  Displays a crisp, clear native resolution of 1280 x 1024 at a 60Hz refresh rate for easy on the eye viewing. Scalable to lower resolutions on demand.
- **Super wide 160° viewing angles**
  Image performance is significantly increased by the wide viewing angle.
- **OnView® controls including ViewMatch®**
  All screen adjustments are made via an on-screen menu using simple controls. ViewMatch allows the user to adjust color temperature and individual color intensity for screen-to-print matching.
- **Slim 3.9" profile (panel only)**
- **Weighs only 17.8 pounds**
- **Available in black**

17" TFT LCD Flat ViewPanel

If you're looking for a large screen flat panel display, yet have limited work space, your search is over – the ViewSonic VE170 ViewPanel is all of that, and much more. It's available at an amazingly affordable price. This 17" TFT display, with its slim 3.9" panel profile, delivers brilliant, bright color-rich images along with sharp, crisp text. And it's available in either the standard light grey color or black. Plus it meets environmental safety standards. The value rich VE170 is the ideal choice for a wide variety of applications, from high end graphics users to the Wall Street trading floor.

ViewSonic on top

ViewSonic®

VE170 LCD Display

• VE170b black case version

- **Detachable base with VESA® wall mount capability**[1]
- **Anti-glare screen**
  This screen treatment refracts unwanted ambient light away from the user while maintaining the highest quality of the displayed image.
- **Kensington® security port**
  Kensington® security port protects your assests.
- ***Plug & Play +***
  Fully supports the Microsoft® Windows® auto-installation standard for easy, trouble-free configuration and setup.
- **TCO '99 and Energy 2000 compliant**[2]
  This display complies with the world's strict standards for low radiation, safety, ergonomics, recycling and power management while saving costs through automatic power savings mode.
- **PC and Mac® compatible**[3]
- **Three year limited warranty and first year Express Exchange® and customer service included**
  24/7 free technical support.

17" VIEWABLE COLOR TFT LCD DISPLAY IN CHOICE OF TWO COLORS

VIEWPANEL	**Type**	SXGA TFT active matrix (16.7 million colors)
	Display Area	13.2" horizontal x 10.6" vertical, 17.0" diagonal
	Contrast Ratio	200:1 (typ)
	Viewing Angle	160° horizontal, 160° vertical (typ)
	Light Source	20,000 hour (min)
	Brightness	200 cd/m² (typ)
	Glass Surface	Anti-glare coat
INPUT SIGNAL	**Video**	RGB Analog (75 ohms, 0.7 Vp-p)
	Frequency	F_h:30-80kHz, F_V:50-85Hz
	Sync	H/V Separated (TTL), composite sync, sync-on-green
COMPATIBILITY	**PC**	PC Compatibles (from VGA up to 1280 x 1024 non interlaced)
	Mac®[3]	Power Mac™ (up to 1280 x 1024)
CONNECTOR	**Analog RGB**	15 pin mini D-sub
	Security	Kensington® security port
POWER	**Voltage**	AC 90-264V (universal) via external DC converter brick
	Consumption	50W (max)
CONTROLS	**Physical**	1, down arrow, up arrow, 2, power (soft)
	OnView®	Contrast, brightness, auto tune, H/V position, phase, H. size, zoom, H/V zoom, H/V OSD position, scaling, ViewMatch® color, sharpness, ViewMeter®, language, OSD timeout, gamma, memory recall
BANDWIDTH	**Video Input**	135 Mhz
OPERATING CONDITION	**Temperature**	32°F to 104°F (0°C to 40°C) 10% to 90% (no condensation)
DIMENSIONS	**Physical**	448mm (W) x 474mm (H) x 229mm (D) 17.64" (W) x 18.66" (H) x 9.02" (D)
WEIGHT	**Net**	8.1 kg (17.82 lbs)
OTHER		DDC1 & DDC2B
REGULATIONS		UL, CSA, FCC-B, CB, CE, DOC-B TUV/ERGO, TUV/GS, TCO '99, ENERGY 2000, TCO '95 (VE170b), VCCI, BSMI, NEMKO, SEMKO, DEMKO, FIMKO, B-MARK, NOM, PCT+HYGIENIC (GOST-R), IRAM, S-MARK, C-TICK, CCIB + CCEE
POWER MANAGEMENT		Meets ENERGY STAR®, VESA® DPMS, and TCO '99 standards
WARRANTY		Three years limited warranty on parts, labor and back light First year Express Exchange® service included

ISO 9001 FM 40187

ISO 14001 EMS 40968

ViewSonic Corporation's QMS\EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ViewSonic on top

381 Brea Canyon Road, Walnut, CA 91789
Phone (800) 888-8583 • (909) 869-7976
Fax (909) 468-1202 • Internet: www.ViewSonic.com

[1]Designed for easy wall mount configuration with any third party wall mount kits that meets VESA wall mount specifications. See third party wall mount manufacturers for additional details. [2]TCO '95 (VE170b). [3]May require the use of the VS cable adapter. Copyright © 2000, ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice. As an ENERGY STAR® partner, ViewSonic has determined that this product meets the Energy Star® guidelines for energy efficiency. Microsoft, Windows, Windows NT, Windows 2000 and the Windows logos are the registered trademarks of Microsoft Corporation in the United States and other countries.

VSVE170_10/00_20k_rev1
VS-2118